

APPLICATION INSTRUCTIONS FOR

To Order: Stahls.com • 800.478.2457 • Fax: 800.346.2216

Canada: Stahls.ca • 800.521.5255

CAD-PRINTZ® Perma-TWILL® & Texture-TWILL™



PREHEAT GARMENT
for 10 seconds, prior to application, to remove moisture and wrinkles.

Detailed designs may arrive pre-positioned with a clear mask. Apply at recommended settings, then peel hot.



POSITION APPLIQUE
and place cover sheet over design. Each application requires a new cover sheet; which is provided.



HEAT APPLY—
Temp: 300°F; 150°C
Time: 20 seconds
Pressure: medium
#6 on Hotronix®

Recommended Fabrics:

Cotton
Polyester

Permanent application with heat press to cotton and polyester. To apply to other fabrics, sewing is required. Embroidery Express Sew Disks options available.

Due to the combination of fabrics, weaves, coatings and dyes used in the textile industry, Stahls' recommends and provides samples of our materials and medias for testing.

Accessories Required:

Cover Sheet
included with order

Care Instructions:

Machine wash warm or cold using mild detergent.
Do not bleach. Tumble dry low.

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Hotronix are trademarks & ® trademarks of STAHL'S' with one or more patents or patents pending.

STAHL'S'® 2014 - All International Rights Reserved